

Specification

ENGINE. Six cylinder 4-2 litre 'XK' engine with twin overhead camshafts and three carburetters, 92-07 mm. bore × 106 mm. stroke. Capacity 4,235 c.c., 255 b.h.p. at 5,400 r.p.m. Compression ratio 8 to 1. Cooling system incorporates cross-flow tube and fin radiator block, fluid drive speed-control fan and improved design water pump.

TRANSMISSION. (Manual) Four-speed all-synchromesh gearbox; gear change lever on floor between front seats. (Overdrive) As above, with addition of a Laycock de Normanville overdrive controlled by lever on steering column. (Automatic) Borg Warner automatic transmission with dual drive range D1/D2. Selector lever on steering column.

SUSPENSION. (Front) Independent suspension — double wishbones, coil springs with telescopic shock absorbers. (Rear) Fully independent suspension incorporating, on each side, a lower transverse link pivoted at wheel carrier and subframe adjacent to differential case and, above this, a half-shaft universally jointed at each end. Twin coil springs each enclose a telescopic hydraulic damper.

BRAKES. Servo-assisted disc brakes all round. Independent hydraulic circuits to front and rear. Self adjusting handbrake.

STEERING. "Variantic" variable ratio power steering. 2:75 turns lock to lock.

WHEELS & TYRES. Pressed steel bolt-on disc wheels. Dunlop 205 mm. × 14 in.

SP41 tyres and tubes.

FUEL SUPPLY. Twin tanks, total capacity 20 gallons. Twin electric pumps. Separate concealed fillers. Change-over switch on facia panel.

ELECTRICAL EQUIPMENT & INSTRUMENTS. Alternator generator. 12-volt battery with negative earth system. Extensive equipment includes — Four headlamp system, headlamp flashing unit, twin reversing lamps, map reading lamp, continental side winkers, cigar lighter, twin-blade two-speed windscreen wipers, windscreen washers, automatic ignition advance, transistorised clock, all fitted as standard. Comprehensive instrumentation to Jaguar normal high standards.


BODY. All steel four-door five-seater saloon. Luxurious upholstery in ventilated leather hide over deep Dunlopillo cushions. Central folding armrests front and rear. Reclining front seats with flush fitting picnic trays in backs of squabs. Deep pile carpets over thick felt underlay. Padded safety screen rail. 27 cubic feet capacity luggage boot.


HEATING & DEMISTING. High output system. Regulation for temperature, volume and direction of air for each side of saloon. Separate ducting to rear compartment.

SPARE WHEEL & TOOLS. Spare wheel housed in luggage boot and fully trimmed to protect luggage. Comprehensive set of tools in special container.

Principal Dimensions · 420 G

Wheelbase 10ft., track front 4ft. 10ins., track rear 4ft. 10ins., overall length 16ft. 10ins., overall width 6ft. 4ins., overall height 4ft. 6½ins., turning circle 37ft.







JAGUAR CARS LIMITED · COVENTRY · ENGLAND


The issue of this catalogue does not constitute an offer. The specification described in this brochure varies for different countries, and Jaguar Cars Ltd. reserve the right to amend specifications at any time without notice. Due to tolerances all measurements and weights in this catalogue are approximate.


The colours printed in this catalogue may differ from actual paint colours. For details of colour range available please consult your local Distributor or Dealer.
















The Jaguar 420Gthe car built around the company director. Sink into your elegant seat. Stretch out your legs. Give the word to your chauffeur. And glide noiselessly away.

Your first sensation is one of space. More than enough room for five large-size adults. And more than enough room for their briefcases, umbrellas, hats and other impedimenta.













