







or both driver and passengers, XJS models provide exceptional comfort, convenience and efficiency.

4-speed electronically controlled automatic gearboxes are fitted as standard and feature easy switching from 'Normal' to 'Sport' modes. A 5-speed manual gearbox is available at no extra cost, cruise control is standard on both models.

Above the six analogue instrument dials is a line of 'secret until lit' warning and advisory lamps. Below the analogue clock, either side of the audio unit, are the extremely simple controls for the standard air conditioning unit, which uses CFC-free refrigerant and

has an air recirculating facility.

The standard audio unit incorporates RDS facilities

which include automatic station retuning and the ability to select

programmes of a particular type, such as music, speech or news.







Trip computer and front fog lamps shawn are optional at extra cost

Jaguars excel in both primary and secondary safety. Exceptional roadholding ability, accurate power-assisted steering and advanced anti-lock braking play a major part in this. The braking system in particular, has been further enhanced. System refinement is improved as is the "feel" provided by the brake pedal itself – accurate, sensitive and eminently controllable.

The XJS body is an immensely strong steel cage with front and rear energyabsorbing members, anti-intrusion door beams and a steel bulkhead isolating the fuel tank. An inertia switch shuts off the fuel supply in the event of a collision.

Most importantly, SRS airbags inflate automatically in a fraction of a second to protect the driver and front passenger in the event of a severe frontal impact.




SPECIFICATIONS	XJS 4.0 COUPE	XJS 4.0 CONVERTIBLE		
ENGINE TYPE	AJ16 in line 6 cylinder	AJ16 in line 6 cylinder		
	Aluminium alloy cylinder	Aluminium alloy cylinder		
	head/block	head/block		
	DOHC	DOHC		
	4 valves/cylinder	4 valves/cylinder		
Displacement (cm²)	3980	3980		
Bore x stroke (mm)	91 x 102	91 x 102		
Compression ratio	10.0:1	10.0:1		
	10.0.1	10.0.1		
Maximum power	220 (177) @ 1700	220 (1771 @ 4700		
DIN BHP (kW) @ rev/min	238 (177) @ 4700	238 (177) @ 4700		
Maximum torque		000 10001 0 1000		
DIN lb.ft (Nm) @ rev/min	282 (382) @ 4000	282 (382) @ 4000		
Combustion chambers	Pent roof	Pent roof		
Ignition system	Electronic	Electronic		
Fuel system	Electronic injection	Electronic injection		
Fuel grade	95 RON unleaded	95 RON unleaded		
TRANSMISSION TYPE	4-speed 5-speed	4-speed 5-speed		
THE STREET STATE OF THE STATE O	auto manual	auto manual		
Tan mana andia	0.73:1 0.76:1	0.73:1 0.76:1		
Top gear ratio		3.54:1 3.54:1		
Final drive ratio	414 111	29.5 28.51		
MPH per 1000 rev/min in top gear	29.0 28.1			
WHEEL TYPE/SIZE	Aerosport alloy 7 x 16in	Aerosport alloy 7 x 16in		
Tyre size	225/55 ZR 16 Sports 225/60 ZR 16 Comfort			
BRAKING SYSTEM	ventilated at front. Safety split front and re-	g system with yaw control. Vacuum assisted 4 wheel disc brakes, ear circuits incorporating fluid level and anti-lock failure warning.		
CTTTTU 10	Hand operated mechanical parking brake on rear wheels.			
STEERING	Rack and pinion power assisted steering. Energy absorbing steering column. Four-spoke (SRS) airbag steering wheel with 4-position vertical adjustment.			
Turns lock to lock	2.76	2.76		
Turning circle between kerbs ft (m)	42.7 (13)	42.7 (13)		
SUSPENSION - FRONT		bones, coil springs and telescopic dampers. Anti-roll bar.		
	Anti-dive geometry providing longitudinal stability under heavy braking. Sports damper settings on coupé.			
	Anti-dive geometry providing longitudina	al stability under heavy braking. Sports damper settings on coupé.		
- RÉAR	Anti-dive geometry providing longituding Fully independent with lower tra			
- REAR	Fully independent with lower tra	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshafts acting as upper links.		
027-438	Fully independent with lower tra Radius arms, twin coil springs ar	al stability under heavy braking. Sports damper settings on coupé. Insverse wishbones and driveshafts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé.		
027-438	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocoque construction.	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. nd telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to		
027-438	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocoque construction. Energy absorbing front and rear crumple zome	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshafts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to A posts, sills, underfloor and bulkheads.		
027-438	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshafts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. Indiscreens. Frameless door glass and direct glazed front windscree		
BODY CONSTRUCTION	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé, Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn	ol stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshafts acting as upper links. Ind telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. Indicate a posts, sills, underfloor and bulkheads. Frameless door glass and direct glazed front windscree Bumpers, bonnet and crumple zones as coupé.		
BODY CONSTRUCTION	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé, Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. Indiscreens. Frameless door glass and direct glazed front windscree est. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment.		
BODY CONSTRUCTION	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. andscreens. Frameless door glass and direct glazed front windscree net. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse point process with automated electrostatic application		
BODY CONSTRUCTION	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to les. A posts, sills, underfloor and bulkheads. andscreens. Frameless door glass and direct glazed front windscree let. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. lasse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal.		
BODY CONSTRUCTION PAINT AND PROTECTION	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. andscreens. Frameless door glass and direct glazed front windscree tel. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application		
PAINT AND PROTECTION PERFORMANCE	Fully independent with lower tra Radius arms, Twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over be of primer and clear coats. Two b Box sections o	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. Brameless door glass and direct glazed front windscree net. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected.		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates)	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. Indiscreens. Frameless door glass and direct glazed front windscreenet. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal.		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates)	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé, Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b Bax sections of	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. andscreens. Frameless door glass and direct glazed front windscree het. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. hase paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected. Automatic Manual		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates) Acceleration –	Fully independent with lower tra Radius arms, Twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over be of primer and clear coats. Two b Box sections o	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. Brameless door glass and direct glazed front windscree net. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected.		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates] Acceleration - 0-60 m.p.h. (0-100 km/h) - sec	Fully independent with lower tra Radius arms, twin coil springs ar Two door coupé, Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b Bax sections of	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. andscreens. Frameless door glass and direct glazed front windscree het. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. hase paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected. Automatic Manual		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates] Acceleration – 0-60 m.p.h. (0-100 km/h) – sec Top speed – m.p.h. (km/h)	Fully independent with lower trace. Radius arms, twin coil springs at Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone. Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane. Cathodic electrocaat. Clear over be of primer and clear coats. Two bears are common and the coats. Two bears are common and the coats. Two bears are constructed and clear coats. Two bears are constructed and coats. The coats are constructed and coats. The coats are constructed and coats. The coats are coats are constructed and coats. The coats are constructed and coats are constructed and coats. The coats are constructed and coats are constructed and coats. The coats are constructed and coats are constructed and coats. The coats are constructed and coats are constructed and coats. The coats are constructed and coats are constructed and coats. The coats are constructed and coats are constructed and coats. The coats are constructed and coats are coats. The coats are coats are constructed and coats are coats. The coats are coats are coats are coats. The coats are coats are coats are coats are coats.	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to les. A posts, sills, underfloor and bulkheads. Indiscreens. Frameless door glass and direct glazed front windscreent. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected. Automatic Manual 8.0 [8.4] 7.2 (7.8)		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates) Acceleration = 0-60 m.p.h. (0-100 km/h) = sec Top speed = m.p.h. (km/h) FUEL CONSUMPTION	Fully independent with lower trac Radius arms, Ivin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocaat. Clear over b of primer and clear coats. Two b Box sections of Automatic Manual 7.6 [8.1] 6.9 (7.6) 147 [237]	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. Frameless door glass and direct glazed front windscree est sinc coated. Zinc phosphate pre-treatment. Lasse paint process with outomated electrostatic application base colour and two clear coats. Bitumen wax underseal. Automatic Manual 8.0 [8.4] 7.2 (7.8) 1.45 [234]		
PAINT AND PROTECTION PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates) Acceleration = 0-60 m.p.h. (0-100 km/h) = sec Top speed = m.p.h. (km/h) FUEL CONSUMPTION Urban cycle = m.p.g. (litres/100 km)	Fully independent with lower trac Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b Box sections of Automatic Manual 7.6 (8.1) 6.9 (7.6) 147 (237) 21.7 (13.0) 18.8 (15.1)	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. case point process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected. Automatic Manual 8.0 (8.4) 7.2 (7.8) 145 (234) 21.7 (13.0) 18.8 (15.1)		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates] Acceleration - 0-60 m.p.h. (0-100 km/h) - sec Top speed - m.p.h. (km/h) FUEL CONSUMPTION Urban cycle - m.p.g. (litres/100 km) 56 m.p.h m.p.g. (litres/100 km)	Fully independent with lower trac Radius arms, twin coil springs ar Two door coupé, Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocast. Clear over b of primer and clear coats. Two b Bax sections of Automatic Manual 7.6 [8.1] 6.9 (7.6) 147 (237) 21.7 (13.0) 18.8 (15.1) 37.9 (7.5) 37.2 (7.6)	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. Frameless door glass and direct glazed front windscreenet. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hat wax injected. Automatic Manual 8.0 [8.4] 7.2 [7.8] 145 [234] 21.7 [13.0] 18.8 [15.1] 37.9 [7.5] 37.2 [7.6]		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates) Acceleration - 0-60 m.p.h. (0-100 km/h) - sec Top speed - m.p.h. (km/h) FUEL CONSUMPTION Urban cycle - m.p.g. (litres/100 km) 75 m.p.h m.p.g. (litres/100 km) 75 m.p.h m.p.g. (litres/100 km) WEIGHT	Fully independent with lower trac Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b Box sections of Automatic Manual 7.6 (8.1) 6.9 (7.6) 147 (237) 21.7 (13.0) 18.8 (15.1)	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. andscreens. Frameless door glass and direct glazed front windscree tel. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. sase paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hot wax injected. Automatic Manual 8.0 (8.4) 7.2 (7.8) 145 (234) 145 (234) 21.7 (13.0) 18.8 (15.1)		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates) Acceleration = 0-60 m.p.h. (0-100 km/h) = sec Top speed = m.p.h. (km/h) FUEL CONSUMPTION Urban cycle = m.p.g. (litres/100 km) 56 m.p.h. = m.p.g. (litres/100 km) 75 m.p.h. = m.p.g. (litres/100 km) WEIGHT Maximum kerb weight =	Fully independent with lower trac Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b Box sections of Automatic Manual 7.6 (8.1) 6.9 (7.6) 147 (237) 21.7 (13.0) 18.8 (15.1) 37.9 [7.5] 37.2 (7.6) 28.6 [9.9] 29.5 (9.6)	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. A posts, sills, underfloor and bulkheads. Prameless door glass and direct glazed front windscree het. Bumpers, bonnet and crumple zones as coupé. Bumpers, bonnet and crumple zones as coupé. Bes zinc coated. Zinc phosphate pre-treatment. Lase paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. Automatic Manual 8.0 (8.4) 7.2 (7.8) 1.45 (234) 21.7 (13.0) 18.8 (15.1) 37.9 (7.5) 37.2 (7.6) 28.6 (9.9) 29.5 (9.6)		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates] Acceleration – 0-60 m.p.h. (0-100 km/h) – sec Top speed – m.p.h. (km/h) FUEL CONSUMPION Urban cycle – m.p.g. (litres/100 km) 56 m.p.h. – m.p.g. (litres/100 km) 75 m.p.h. – m.p.g. (litres/100 km) WEIGHT Maximum kerb weight – Ib (kg) with options	Fully independent with lower trac Radius arms, twin coil springs ar Two door coupé, Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocast. Clear over b of primer and clear coats. Two b Bax sections of Automatic Manual 7.6 [8.1] 6.9 (7.6) 147 (237) 21.7 (13.0) 18.8 (15.1) 37.9 (7.5) 37.2 (7.6)	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links. Ind telescopic dampers. Sports damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. Frameless door glass and direct glazed front windscreenet. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hat wax injected. Automatic Manual 8.0 [8.4] 7.2 [7.8] 145 [234] 21.7 [13.0] 18.8 [15.1] 37.9 [7.5] 37.2 [7.6]		
PAINT AND PROTECTION PERFORMANCE [Manufacturer's estimates) Acceleration = 0-60 m.p.h. (0-100 km/h) = sec Top speed = m.p.h. (km/h) FUEL CONSUMPTION Urban cycle = m.p.g. (litres/100 km) 56 m.p.h. = m.p.g. (litres/100 km) WEIGHT Maximum kerb weight =	Fully independent with lower trac Radius arms, twin coil springs ar Two door coupé. Monocaque construction. Energy absorbing front and rear crumple zone Frameless door glass, direct glazed front and rear wir Wrap around bumpers. Forward hinged bonn All critical body pane Cathodic electrocoat. Clear over b of primer and clear coats. Two b Box sections of Automatic Manual 7.6 (8.1) 6.9 (7.6) 147 (237) 21.7 (13.0) 18.8 (15.1) 37.9 [7.5] 37.2 (7.6) 28.6 [9.9] 29.5 (9.6)	al stability under heavy braking. Sports damper settings on coupé. ansverse wishbones and driveshofts acting as upper links, and telescopic dampers. Sparts damper settings on coupé. Two door convertible. Structural stiffening added to es. A posts, sills, underfloor and bulkheads. and posts, sills, underfloor and bulkheads. Bumpers, bonnet and crumple zones as coupé. els zinc coated. Zinc phosphate pre-treatment. asse paint process with automated electrostatic application base colour and two clear coats. Bitumen wax underseal. and closed members hat wax injected. Automatic Manual 8.0 (8.4) 7.2 (7.8) 1.45 (234) 21.7 (13.0) 18.8 (15.1) 37.9 [7.5] 37.2 (7.6) 28.6 [9.9] 29.5 (9.6)		

DIMENSIONS

	XJS 4.0 COUPE	XJS 4.0	
A	Overall length in. (mm) 189.8 (4820)	189.8 (4820)	
В	Overall width including mirrors in. (mr 74.1 (1983) Overall width excluding mirrors in. (m 70.6 (1793)	74.1 [1883]	
c	Overell height in. (mm) 48.9 (1241)	50.2 [1276]	
D	Ground dearance - minimum at GVV 4.7 (120)	V in. (mm) 4.7 (120)	
E	Track width - front in. (mm) 58.6 (1489)	58.6 (1489)	
F	Track width – rear in. (mm) 59.2 (1504)	59.2 (1504)	
G	Wheelbase in. (mm) 101.9 (2588)	101.9 (2588)	
н	Maximum legroom - front driver in. (r 43.0 (1091)	mm) 43.0 (1091)	
ı	Maximum legroom - front passenger 43.9 (1114)	in. (mm) 43.9 (1114)	
J	Minimum legroom – rear outboard in. 23.4 (594)	(mm) 23.3 (592)	
K	Maximum headroom – front in. (mm) 36.1 (917)	35.7 (906)	
L	Maximum headroom – rear in. (mm) 33.4 (848)	31.1 (790)	
M	Shoulder width – front in. (mm) 56.1 (1425)	56.1 (1425)	
N	Shoulder width - rear in. (mm) 53.0 (1346)	46.1 (1171)	
0	Boot volume ou ft (m ³) – usable 10.26 (0.29)	9.66 (0.27)	
P	Fuel tank capacity Imp. gal. (litres) 19.6 (89)	17.5 (80)	
P		17.	5 (80)

Note: Dimensions refer to a standard car but may vary marginally from car to car due to design and production tolerances. The cominal condition has been used wherever possible. Please cansulty your dealer for details of changes associated with option firment.



This brochure describes the general features of the Jaguar XJ5 range. However, specifications and availability do vary from country to country and its therefore essential to refer to your dealer for specific data's of the cars available in any particular country.



The calcurs are intended to serve primarily as a guide and while they approximate to the actual shades they should not be utilised for paint matching or for any other purpose where complete accuracy is



INTERIOR TRIM

All models are fitted as standard with a colour keyed facia. To examine the actual quality of Jaguar upholstery materials please consult your Jaguar dealer's colour and upholstery book.


For details of available colour/trim combinations and extra costs for certain paint finishes and upholstery materials (where applicable), please consult your dealer and the current Jaguar Price List.

A Charcoal facia may be specified at the time of ordering for no extra cost.

Seat Trim Colour	Contrast Piping	
Oatmeal	Antelope	
Coffee	Cream	
Nimbus Grey	Slate	
Regatta Blue	Warm Charcoal	
Parchment	Sage Green	
Cream	Coffee	
Warm Charcoal	Nimbus Grey	

PARCHMENT LEATHER





NIMBUS GREY LEATHER REGATTA BLUE LEATHER





COFFEE LEATHER WARM CHARCOAL LEATHER



WARM CHARCOAL FACIA

CONVERTIBLE HOOD COLOURS



BLACK



BURGUNDY





BEIGE





Jaguar Cars Limited Browns Lane Allesley Coventry CV5 9DR England







Important Notice
Jaguar Cars Limited is constantly seeking ways to improve the specification, design and production of its vehicles and alterations take place continually. Whilst every effort is made to produce up to date literature, this brochure should not be regarded as an infallible guide to current specifications, nor does it constitute an offer for the sale of any particular vehicle.

Distributors and dealers are not agents of Jaguar Cars Limited and have absolutely no authority to bind Jaguar Cars Limited by any express or implied undertaking or representation.



ince the first SS Jaguar 1½ and 2½ litre sports saloons of 1935, a host of famous sporting Jaguars have been introduced, all of them now world-famous classics:

\$\$100 (1936) XK120 (1948) C-type (1951) XK 140 (1954) D-type (1954) XK 150 (1957) XKSS (1957) E-type (1961) V12 E-type (1971)

Yet despite the justified fame of these wonderful models, the most popular and successful of all Jaguar sporting cars has proved to be the XJS.

Right from the beginning, the philosophy of Jaguar founder Sir William Lyons was to after cars for "discriminating purchasers who wish to have in their possession something really exclusive in modern design at a very reasonable figure". Nothing could more perfectly describe the latest XJS, which is more attractive and more generously equipped than ever.

To commemorate 60 glorious years of sports car prowess, Jaguar are pleased to announce two 'celebration' models offering more excitement, distinction and value for money than ever before.

No other cars – at any price – possess the unique combination of Jaguar style, prestige, performance, engineering perfection and luxury.

The latest 4.0 litre XJS Coupés and Convertibles have the brilliant new AJ16 doubleoverhead camshaft 6-cylinder engine that has been the subject of such acclaim in the new XJ Series Jaguar saloons. Offering a smooth and silky power delivery, this engine provides a unique combination of virtues.

The standard specification of XJS 4.0 litre models is now even more luxurious. Both coupé and convertible models now feature automatic transmission, cruise control and a walnut and leather interior, reaffirming Jaguar's reputation for affordable luxury.

The two new XJS models: sumptuously sporting, astonishingly attainable and benefiting in every way from Jaguar's 60 years' experience of producing outstanding motor cars.

















he coupé interior continues the XJS theme
of sporting character combined with exceptional
comfort and luxury.

Both 'celebration' XJS models have a 2+2 layout and now have sumptuous leather seats with contrast piping (cloth inserts can be specified at no extra cost). The console lid is trimmed in leather and the head restraints have a distinctive embossed Jaguar 'leaper'. Both front seats are electronically adjustable for recline angle and fore-and-aft movement; heated seats, electric lumbar support and memory control are optional at extra cost.

Jaguar's traditional hand-crafted wood is featured on both 'celebration' XJS models, using figured sapwood walnut veneers and a solid wooden gearknob.



